²⁰²² KLX®110R L







POWER

| Engine | 4-stroke single, SOHC, air-cooled |
|----------------------|--|
| Displacement | 112cc |
| Bore x Stroke | 53.0 x 50.6mm |
| Compression Ratio | 9.5:1 |
| Fuel System | 18mm Keihin carburetor and screw type throttle limiter on grip housing |
| Ignition | DC-CDI |
| Transmission | 4-speed, return shift, wet multi-disc manual clutch |
| Final Drive | Chain |
| | |

Rear Tire3.00x12Front Brakes90mm mechanical drum, cable actuatedRear Brakes110mm mechanical drum, rod actuated

DETAILS

| | Frame Type | Backbone frame, high-tensile steel |
|----|----------------------|------------------------------------|
| | Rake/Trail | 24.2°/1.9 in |
| | Overall Length | 61.4 in |
| | Overall Width | 25.6 in |
| | Overall Height | 39.0 in |
| | Ground Clearance | 10.4 in |
| | Seat Height | 28.7 in |
| | Curb Weight | 167.5 lb* |
| | Fuel Capacity | 1.0 gal |
| | Wheelbase | 42.3 in |
| .2 | Color Choices | Lime Green |
| | Warranty | 6 Months |
| | | |

PERFORMANCE

| Front Suspension / Wheel Travel | 30mm hydraulic telescopic fork/5.5 in |
|---------------------------------------|---|
| Rear Suspension / Wheel Travel | Swingarm with single hydraulic shock/5.2 in |
| Front Tire | 2.50x14 |





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.