## <sup>2022</sup> KLX®140R L







## POWER

			Front Brakes	
Engi	ine	4-stroke single, SOHC, air-cooled		
Disp	olacement	144cc	Rear Brakes	
Bore	e x Stroke	58.0 x 54.4mm		
Com Rati	pression o	9.5:1	DETAILS	
Fuel	System	20mm Keihin carburetor	Frame Type	
Ignit	-	Digital DC-CDI	Rake/Trail	
Transmission	smission	5-speed, return shift, with wet multi-disc manual clutch	Overall Length	
			Overall Width	
Fina	l Drive	Chain	Overall Height	
Ground Ground				

## PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in
Front Tire	70/100-19

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with a dual- piston caliper
Rear Brakes	Single 186mm petal disc with single- piston caliper

	Frame Type	High-tensile steel, box-section perimeter		
isc	Rake/Trail	27°/3.8 in		
	<b>Overall Length</b>	74.6 in		
	Overall Width	31.1 in		
	Overall Height	42.3 in		
	Ground Clearance	10.0 in		
nock ole /7.1	Seat Height	31.5 in		
	Curb Weight	209.4 lb*		
	Fuel Capacity	1.5 gal		
	Wheelbase	50.6 in		
	Color Choices	Lime Green		
	Warranty	6 Months		





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.