

2023

KLR® 650 TRAVELER ABS



POWER		Rear Tire	130/80-17
Engine	4-Stroke, single cylinder, DOHC	Front Brakes	Single 300mm disc with 2-piston calipers, ABS
Displacement	652cc	Rear Brakes	Single 240mm disc with single-piston caliper, ABS
Bore x Stroke	100.0 x 83.0mm	DETAILS	
Compression Ratio	9.8:1	Frame Type	Tubular, Semi-Double Cradle
Maximum Torque	39.1 lb.-ft. @ 4,500rpm	Rake/Trail	30.0° / 4.8 in
Fuel System	DFI w/40mm Throttle Body	Overall Length	89.8 in
Ignition	CDI	Overall Width	38.2 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	57.7/56.3 in (screen hi/lo)
Final Drive	Sealed Chain	Ground Clearance	8.3 in
PERFORMANCE		Seat Height	34.3 in
Front Suspension / Wheel Travel	41mm telescopic fork/ 7.9 in	Curb Weight	471.7 lb*
Rear Suspension / Wheel Travel	Uni-Trak®, single shock with adjustable rebound damping and adjustable spring preload / 8.0 in	Fuel Capacity	6.1 gal
Front Tire	90/90-21	Wheelbase	60.6 in
		Color Choices	Pearl Solar Yellow
		Warranty	12 Months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [panama.kawasaki-la.com](http://panama.kawasaki-la.com) for full product details.