## <sup>2023</sup> **KX™85**







## POWER

2-stroke single with exhaust power valve (KIPS), liquid-cooled
84cc
48.5 x 45.8mm
10.9:1 (low speed) - 9.0:1 (high speed)
28mm Keihin carburetor
CDI with digital advance
6-speed, return shift, with wet multi-disc manual clutch
Chain

## PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in
Front Tire	70/100-17

Rear Tire	90/100-14
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 184mm petal disc with single-piston caliper

## **DETAILS**

	Frame Type	High-tensile steel perimeter design with subframe member
	Rake/Trail	29°/3.8 in
:	<b>Overall Length</b>	72.0 in
	Overall Width	30.1 in
	<b>Overall Height</b>	43.3 in
	Ground Clearance	11.4 in
in	Seat Height	32.7 in
	Curb Weight	165.3 lb*
ay	Fuel Capacity	1.32 gal
	Wheelbase	49.8 in
	Color Choices	Lime Green
	Warranty	Not Available





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.