
2024 **VULCAN® 900 CUSTOM**









POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire 80/90-21 **Rear Tire** 180/70-15 Single 300mm hydraulic disc **Front Brakes** Single 270mm hydraulic disc **Rear Brakes**

DETAILS

58.2 lb-ft @ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	33°/7.2 in
DFI® with 34mm throttle bodies (2), with sub-throttle valves	Overall Length	94.7 in
TCBI with Electronic Advance	Overall Width	35.2 in
5-speed with positive neutral finder	Overall Height	44.1 in
Kevlar-reinforced belt	Ground Clearance	5.5 in
ANCE	Seat Height	27.0 in
	Curb Weight	610.8 lb*
41mm Showa telescopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Color Choices	Metallic Matte Dark Gray/Metallic Flat Spark Black
	Warranty	12 Month Limited Warranty

PERFORMANCE

Front	
Suspension /	
Wheel Travel	

Rear Suspension / Wheel Travel

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.