2024 **BRUTE FORCE® 300**









Engine4-stroke, 1-cylinder, SOHCElectronic Power Steering (EPS)NoDisplacement271ccTurning Radius9.2 ftBore x Stroke72.7 x 65.2mmTowing Capacity500 lbCompression Ratio11.0:1Total Rack Capacity110 lbMaximum Torque15.9 lb-ft @ 6,500 rpmRack Capacity, Front/Rear44/66 lbIgnitionDC-CDILighting(2) 35W headling	
Bore x Stroke72.7 x 65.2mmTowing Capacity500 lbCompression Ratio11.0:1Total Rack Capacity110 lbMaximum Torque15.9 lb-ft @ 6,500 rpmRack Capacity, Front/Rear44/66 lb	
Compression Ratio11.0:1Total Rack Capacity110 lbMaximum Torque15.9 lb-ft @ 6,500 rpmRack Capacity44/66 lbFuel SystemKeihin CVK32 carburetorFront/Rear44/66 lb	
Compression RatioH.G.TCapacityMaximum Torque15.9 lb-ft @ 6,500 rpmRack Capacity, Front/Rear44/66 lbFuel SystemKeihin CVK32 carburetorFront/Rear44/66 lb	
Maximum Torque15.9 lb-ft @ 6,500 rpmRack Capacity, Front/Rear44/66 lbFuel SystemKeihin CVK32 carburetorFront/Rear	
Fuel System Keihin CVK32 carburetor Front/Rear	
Ignition DC-CDI Lighting (2) 35W headli	
Transmission Automatic CVT with centrifugal clutch (H,L,N,R)	
Final Drive 2WD, Shaft	

CAPABILITY

Front Suspension / Wheel Travel	Independent double wishbone/5.2 in	C
Rear Suspension / Wheel Travel	Swingarm/5.6 in	C
Front Tires	AT 22 x 7-10 Maxxis® tubeless	5
Rear Tires	AT 22 x 10-10 Maxxis® tubeless	C
Front Brakes	Dual 148mm discs	V
Rear Brakes	Single 148mm disc	l
Ground Clearance	6.1 in	0
Starting System	Electric	v
		v

Towing Capacity	500 lb	
Total Rack Capacity	110 lb	
Rack Capacity, Front/Rear	44/66 lb	
Lighting	(2) 35W headlights, 5W taillight and 21W stoplight	
DETAILS		
Eramo Tuno	Double gradle, steel	

Frame Type	Double cradle, steel
Track Front/Rear	33.5/32.7 in
Overall Length	75.4 in
Overall Width	42.5 in
Overall Height	46.1 in
Seat Height	33.3 in
Curb Weight	535.8 lb*
Wheelbase	45.9 in
Instruments	Speedometer, odometer, clock, fuel gauge and coolant temp light
Color Choices	Firecracker Red, Grayish Blue
Warranty	12 Month Limited Warranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.