

2024 KX™ 65

Kawasaki
Let the Good Times Roll®



POWER

Engine	2-stroke single, liquid-cooled
Displacement	64cc
Bore x Stroke	44.5 x 41.6mm
Compression Ratio	8.4:1
Fuel System	24mm Mikuni carburetor
Ignition	CDI with Digital Advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	80/100-12
Front Brakes	Single 180mm disc with single-piston caliper
Rear Brakes	Single 180mm disc with single-piston caliper

PERFORMANCE

Front Suspension / Wheel Travel	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in
Front Tire	60/100-14

DETAILS

Frame Type	High-tensile steel semi-double cradle
Rake/Trail	27° / 2.4 in
Overall Length	62.6 in
Overall Width	29.9 in
Overall Height	37.6 in
Ground Clearance	12.0 in
Seat Height	29.9 in
Curb Weight	132.2 lb*
Fuel Capacity	1.0 gal
Wheelbase	44.1 in
Color Choices	Lime Green
Warranty	Not Available

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.