NINJA® ZX™-10R







P	N	١	N	F	R
	u			_	

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

13.0:1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

Fuel System DFI® with 47mm throttle bodies

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner

Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with Balance Free gascharged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual

radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

(ABS only)

Rear Brakes Single 220mm disc with aluminum single-piston

caliper, Kawasaki Intelligent anti-lock Brake

System (KIBS) (ABS only)

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.1 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb* (ABS), 452.0 lb* (non-ABS)

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Flat Spark Black/Ebony

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

