NINJA® ZX™-4RR ABS







P	N	W	/F	R
	u			•

Engine 4-stroke, In-Line Four, OHC, 16-valve, liquid-

cooled

Displacement 399cc

Bore x Stroke 57.0 x 39.1mm

Compression

Ratio

12.3:1

Fuel System DFI® with 34mm throttle valves (4)

Ignition Digital

Transmission 6-speed, manual, return shift

Final Drive Chain

Electronic Rider Aids Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel 37mm inverted fork with SFF-BP internals and spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9

in

Front Tire 110/70-17

Rear Tire 160/60-17

Front Brakes Dual 290mm discs, ABS

Rear Brakes Single 220mm disc, ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 23.5°/3.8 in

Overall Length 78.3 in

Overall Width 30.1 in

Overall Height 43.7 in

Ground 5.3 in Clearance

Seat Height 31.5 in

Curb Weight 414.5 lb*

Fuel Capacity 4.0 gal

Wheelbase 54.3 in

Special Features 4.3" Full-Color TFT Instrumentation,

Smartphone Connectivity via RIDEOLOGY THE

APP

Color Choices Metallic Spark Black

Warranty 12 Month Limited Warranty

