2024 **TERYX KRX® 1000 eS**





ICE GRAY/METALLIC ONYX BLACK



POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	
Displacement	999cc	
Maximum Torque	76.7 lb-ft @ 7,000 rpm	
Bore x Stroke	92.0 x 75.1mm	
Compression Ratio	11.5:1	
Fuel System	DFI® with two 50mm throttle bodies	
Ignition	TCBI with Electronic Advance	
Starting System	Electric	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	
Engine Braking	Yes	

Turning Radius	20.3 ft
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lb
Payload Capacity	781 lb
Seating Capacity	2
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel	
Selectable 2WD/4WD with locking front differential, shaft	Overall Length	132.1 in	
Yes	Overall Width	68.1 in	
	Overall Height	77.0 in	
	Curb Weight	1,944.8 lb* / 1,947.0 lb* CA Model	
Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and	Wheelbase	98.8 in	
KECS controlled compression damping/18.6 in	Instruments	Multi-function digital meter with bar-style tachometer (2	
4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in		display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature,	
Maxxis® Carnivore 31 x 10.00R15 8PR		seatbelt warning lamp, oil warning lamp, engine check lamp,	
Maxxis® Carnivore 31 x 10.00R15 8PR		water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning	
Electric Power Steering (EPS) / rack-and-pinion		lamp, and CVT belt warning lamp.	
Dual hydraulic discs with two-piston calipers	Wheel Type	Alloy with bead-lock wheels	
Dual hydraulic discs with single-piston calipers	Additional Features	Roof, Front Bumper	
14.4 in (max), 14.0 in (std)	Color Choices	Ice Gray/Metallic Onyx Black	
10.6 gal	Warranty	6 Month Limited Warranty	



Ground Clearance

CAPABILITY

Front Suspension / Wheel Travel

Rear Suspension /

Wheel Travel

Front Tires

Rear Tires

Steering **Front Brakes**

Rear Brakes

Fuel Capacity



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit panama.kawasaki-la.com for full product details.