## 2025 VULCAN<sup>®</sup> 900 CUSTOM





CANDY FIRE RED/EBONY



## POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire	80/90-21
Rear Tire	180/70-15
Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc

## **DETAILS**

	Frame Type	Semi-double cradle, high-tensile steel
(2), with nder	Rake/Trail	33°/7.2 in
	Overall Length	94.7 in
	Overall Width	35.2 in
	Overall Height	44.1 in
	Ground Clearance	5.5 in
	Seat Height	27.0 in
) in	Curb Weight	610.8 lb*
	Fuel Capacity	5.3 gal
stable	Wheelbase	64.8 in
	Color Choices	Candy Fire Red/Ebony
	Warranty	12 Month Limited Warranty

## PERFORMANCE

		Curb Weight	010.0 เม
Front Suspension / Wheel Travel Rear Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in	Fuel Capacity	5.3 gal
		Wheelbase	64.8 in
	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	<b>Color Choices</b>	Candy Fire F
		Warranty	12 Month Lir

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.