KLX[®]230R S









POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled **Displacement** 233cc **Bore x Stroke** 67.0 x 66.0mm Compression 9.4:1 Ratio DFI® with 32mm Keihin throttle body **Fuel System** Ignition TCBI with electronic advance **Transmission** 6-speed, return shift with wet multi-disc manual clutch

Rear Tire	100/100-18
Front Brakes	Single 240mm petal disc with a dual- piston caliper
Rear Brakes	Single 220mm petal disc with single-

piston caliper

DETAILS

Frame Type

Rake/Trail 24.6°/3.9 in **Overall Length** 80.5 in **Overall Width** 33.3 in **Overall Height** 46.7 in Ground 10.6 in Clearance **Seat Height** 34.4 in **Curb Weight** 262.4 lb* / 264.5 lb* 50-State Model **Fuel Capacity** 1.7 gal Wheelbase 53.3 in

Lime Green, Battle Gray

6 Month Limited Warranty

High-tensile steel, box-section perimeter

PERFORMANCE

Chain

Final Drive

Front
Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Wheel Travel

Front Tire

80/100-21





Color Choices

Warranty