## **KLX®230 S**









D	N	V	V	С	D
Г	U	٧	v	C	π

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Torque 13.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

**Electronic Rider** 

Aids

**Rear Brakes** 

Single 220mm petal disc with single-piston caliper (and ABS)

## **DETAILS**

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 33.3 in

Overall Height 44.9 in

Ground 9.4 in Clearance

Cicaranice

Seat Height 33.3 in

**Estimated Dry** 

Weight

275.6 lb\*\* (ABS), 273.4 lb\*\* (non-ABS) / 277.7 lb\*\* (ABS), 275.5 lb\*\* (non-ABS) 50-State Model

Curb Weight 291.1 lb\* (ABS), 288.9 lb\* (non-ABS) / 293.3 lb\* (ABS), 291.1 lb\* (non-ABS) 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

**Color Choices** 

Warranty

Lime Green

12 Month Limited Warranty

## **PERFORMANCE**

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

2.75 x 21

Rear Tire 4.10 x 18

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Anti-lock Brake System (ABS)



