²⁰²⁵ KLX[®]230SM ABS







Front Brakes Single 300mm petal disc with a dual-piston **POWER** caliper and ABS **Rear Brakes** Single 220mm petal disc with single-piston Engine 4-stroke single, SOHC, air-cooled caliper and ABS Displacement 233cc DETAILS **Bore x Stroke** 67.0 x 66.0mm Compression 9.4:1 Frame Type Perimeter, high-tensile steel Ratio 24.9°/3.0 in Rake/Trail **Maximum Torque** 13.0 lb-ft @ 6,400 rpm **Overall Length** 80.1 in **Fuel System** DFI® with 32mm throttle body **Overall Width** 33.3 in Ignition TCBI with Electronic Advance **Overall Height** 44.3 in Transmission 6-speed Ground 8.7 in **Final Drive** Sealed chain Clearance **Electronic Rider** Anti-lock Brake System (ABS) **Seat Height** 33.1 in Aids **Estimated Dry** 284.4/286.5 lb** 50-State Model PERFORMANCE Weight **Curb Weight** 299.9/302.1 lb* 50-State Model Front Suspension 37mm telescopic fork/7.4 in **Fuel Capacity** 2.0 gal

/ Wheel Travel	
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	110/70-17
Rear Tire	120/70-17

to view videos, key features and more.

Scan with camera

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. @2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.

53.7 in

APP MOTORCYCLE

12 Month Limited Warranty

Battle Gray

ERGO-FIT[®], LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE

Wheelbase

Special Features

Color Choices

Warranty