KLX®300R









4.6 x 18

piston caliper

piston caliper

Single 270mm petal disc with a dual-

Single 240mm petal disc with single-

POWER

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

coote

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.0:1

Fuel System DFI® with 34mm Keihin throttle body

Ignition TCBI with electronic advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type Semi-double cradle

Rake/Trail 26.9°/4.3 in

Overall Length 86.6 in

Overall Width 32.5 in

Overall Height 49.0 in

Ground Clearance 11.8 in

Seat Height 35.4 in

Curb Weight 282.2 lb* / 286.7 lb* 50-State Model

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

Color Choices Lime Green, Battle Gray

Warranty 6 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

43mm inverted telescopic fork with adjustable compression damping/11.2 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in

spring pretoau, 11.2

Front Tire 3.0 x 21

Scan with camera to view videos, key features and more.

