

2025

KX™ 250X



 LIME GREEN



POWER		Rear Tire	110/100-18
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Displacement	249cc	Rear Brakes	Single 240mm Braking petal disc with single-piston caliper
Bore x Stroke	78.0 x 52.2mm	DETAILS	
Compression Ratio	14.0:2	Frame Type	Aluminum perimeter
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors	Rake/Trail	27.5° / 4.8 in
Ignition	Digital DC-CDI	Overall Length	85.8 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation	Overall Width	32.3 in
Final Drive	Chain	Overall Height	49.6 in
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode	Ground Clearance	13.0 in
PERFORMANCE		Seat Height	37.2 in
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping /12.0 in	Curb Weight	233.2 lb* without fuel / 243.2 lb*
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.1 in	Fuel Capacity	1.64 gal
Front Tire	80/100-21	Wheelbase	58.5 in
		Special Features	Smartphone Connectivity via RIDELOGY THE APP KX, ERGO-FIT®
		Color Choices	Lime Green
		Warranty	Not Available

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.