





<b>POWER</b>	P	0	W	E	R
--------------	---	---	---	---	---

Engine 2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

**Compression** Ratio

10.9:1 (low speed) / 9.0:1 (high speed)

Fuel System 28m

28mm Keihin carburetor

Ignition

CDI with Digital Advance

**Transmission** 

6-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

## **PERFORMANCE**

Front Suspension / Wheel Travel 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17

**Rear Tire** 

90/100-14

Front Brakes

Single 220mm petal disc with dual-piston

caliper

**Rear Brakes** 

Single 184mm petal disc with single-piston

caliper

## **DETAILS**

Frame Type High-tensile steel perimeter design with subframe member

Rake/Trail 29.0°/3.8 in

Overall Length 72.0 in

Overall Width 30.1 in

Overall Height 43.3 in

Ground 11.4 in

Seat Height 32.7 in

Curb Weight 164.4 lb\*

Fuel Capacity 1.32 gal

Wheelbase 49.8 in

Special Features

Clearance

ERGO-FIT®

**Color Choices** Lime Green

**Warranty** Not Available

Scan with camera to view videos, key features and more.

