MULE™ 4010 TRANS4x4®







Drum



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

CAPABILITY

(max)

23 amp

itear braites	Diam.
Ground Clearance	7.1 in
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)
Payload Capacity	1,330 lb
Seating Capacity	2-4
Towing Capacity	1,200 lb

DETAILS

Front Suspension / MacPherson Strut/3.9 in

Wheel Travel

Rear Suspension / DeDion Axle/2.8 in **Wheel Travel**

Front Tires 23 x 11-10 **Rear Tires** 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, mechanical drum

Front Brakes Drum Instruments

Color Choices

Warranty Kawasaki STRONG 3-Year Limited Warranty

128.5 in

58.5 in

75.8 in

85.2 in

1,587.6 lb*

Lighting

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Rear Brakes

Timberline Green, Dark Royal Red

Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

(2) Halogen headlights, (2) tail/brake lights

Scan with camera to view videos, key features and more.



