MULE PRO-DXT™ FE EPS









POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 55 amp

(max)

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

999 lb (3-person) / 350 lb (6-person)

person)

7.9 gal

Capacity **Payload Capacity**

Cargo Bed Load

Fuel Capacity

1,574 lb

Seating Capacity 3-person (1-row), 6-person (2-row)

Towing Capacity

2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Wheel Travel

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12 **Rear Tires** 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

Independent, mechanical disc **Park Brake Type**

Front Brakes Dual disc, 2-piston caliper

Dual disc, 1-piston caliper

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in

79.5 in **Overall Height**

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

Rear Brakes



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.