

2025

NINJA® ZX™-10R

Kawasaki
Let the Good Times Roll®



 METALLIC FLAT SPARK BLACK/EBONY



POWER		DETAILS	
Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled	Front Tire	120/70 ZR17
Displacement	998cc	Rear Tire	190/55 ZR17
Bore x Stroke	76.0 x 55.0mm	Front Brakes	Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Compression Ratio	13.0:1	Rear Brakes	Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Maximum Horsepower	196.0 hp ¹ @ 11,500 rpm		
Fuel System	DFI® with 47mm throttle bodies		
Ignition	TCBI with Digital Advance		
Transmission	6-speed, return shift		
Final Drive	Sealed chain		
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)		
PERFORMANCE		Frame Type	Aluminum perimeter
Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in	Rake/Trail	25.0° /4.1 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in	Overall Length	82.1 in
		Overall Width	29.5 in
		Overall Height	46.7 in
		Ground Clearance	5.3 in
		Seat Height	32.9 in
		Curb Weight	456.4 lb* (ABS), 452.0 lb* (non-ABS)
		Fuel Capacity	4.5 gal
		Wheelbase	57.1 in
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Metallic Flat Spark Black/Ebony
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit panama.kawasaki-la.com for full product details.