RIDGE® RANCH EDITION







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

3, bench seat

All-LED lighting

2.500 lb



POWER

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5.500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 FFI **Fuel System**

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 126.4 in **Overall Width** 64.0 in **Overall Height** 81.9 in

Estimated Dry Weight 1,810.3/1,812.5 lb** CA Model **Curb Weight** 1,911.7/1,913.9 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving

Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water

temperature)

Additional Features

WARN® VRX 45 Powersport Winch, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

Color Choices Metallic Stardust White

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Front Tires

Duro 27 x 9-14 **Rear Tires** Duro 27 x 11-14

Wheel Type 14" Aluminum

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes Dual hydraulic 249mm discs with single-piston calipers

Long-Travel, Double Wishbone/12.7 in

Ground Clearance 12.6/13.6 in (max preload); 12.6 in CA Model

Scan with camera to view videos, key features and more.

