



2025

TERYX® KRX4™ 1000



-  METALLIC LIGHT GRAY/SUPER BLACK
-  METALLIC SIERRA BLUE/SUPER BLACK



POWER		Turning Radius	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	23.3 ft
Displacement	999cc	Cargo Bed Load Capacity	14.6 x 33.1 x 9.1 in
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Payload Capacity	351 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	1,001 lb
Compression Ratio	11.5:1	Towing Capacity	4
Fuel System	DFI® with (2) 50mm throttle bodies	Lighting	N/A
Ignition	TCBI with Electronic Advance		(2) LED headlights, (2) LED taillights, LED stoilight
Starting System	Electric	DETAILS	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Length	157.3 in
Engine Braking	Yes	Overall Width	68.1 in
		Overall Height	76.2 in
		Curb Weight	2,099.2 lb* / 2,101.4 lb* CA Model
		Wheelbase	125.8 in
		Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
		Additional Features	Steel skid-plates w/ drain holes
		Color Choices	Metallic Light Gray/Super Black, Metallic Sierra Blue/Super Black
		Warranty	6 Month Limited Warranty
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in		
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in		
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR		
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR		
Steering	Electric Power Steering (EPS) / rack-and-pinion		
Front Brakes	Dual hydraulic discs with 2-piston calipers		
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.8 in (max), 14.2 in (std)		
Fuel Capacity	10.6 gal		

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [panama.kawasaki-la.com](https://panama.kawasaki-la.com) for full product details.