

2025

VERSYS® 1100 SE ABS

Kawasaki

Let the Good Times Roll®



METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK



POWER

| | |
|-----------------------|---|
| Engine | 4-stroke, in-line 4-cylinder, DOHC, liquid-cooled |
| Displacement | 1,099cc |
| Bore x Stroke | 77.0 x 59.0mm |
| Compression Ratio | 11.8:1 |
| Maximum Horsepower | 133.0 hp ¹ @ 9,000 rpm |
| Maximum Torque | 82.5 lb-ft @ 7,600 rpm |
| Fuel System | DFI® with 38mm throttle bodies (4) |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch |
| Final Drive | Chain |
| Electronic Rider Aids | Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness |

PERFORMANCE

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in |
| Rear Suspension / Wheel Travel | Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in |

| | |
|--------------|---|
| Front Tire | 120/70-17 |
| Rear Tire | 180/55-17 |
| Front Brakes | Dual 310mm petal discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) |
| Rear Brakes | Single 260mm petal disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) |

DETAILS

| | |
|----------------------|--|
| Frame Type | Twin-tube, aluminum |
| Rake/Trail | 27.0° / 4.0 in |
| Overall Length | 89.4 in |
| Overall Width | 37.4 in |
| Overall Height | 60.2 in (windshield Hi) / 59.8 in (windshield Lo) |
| Ground Clearance | 5.9 in |
| Seat Height | 33.1 in |
| Estimated Dry Weight | 520.4 lb** (+20 lb w/ saddlebags) |
| Curb Weight | 571.1 lb* (+20 lb w/ saddlebags) |
| Fuel Capacity | 5.5 gal |
| Wheelbase | 59.8 in |
| Special Features | Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, USB Type-C outlet, Adjustable windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice Command via RIDEOLGY THE APP MOTORCYCLE |
| Color Choices | Metallic Graphite Gray/Metallic Diablo Black |
| Warranty | 24 Month Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit panama.kawasaki-la.com for full product details.