

# 2025 Z650

**Kawasaki**  
Let the Good Times Roll®



METALLIC SPARK BLACK/GREEN



METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK



## POWER

<b>Engine</b>	4-stroke, 2-cylinder, DOHC, liquid-cooled
<b>Displacement</b>	649cc
<b>Bore x Stroke</b>	83.0 x 60.0mm
<b>Compression Ratio</b>	10.8:1
<b>Maximum Horsepower</b>	67.0 hp <sup>1</sup> @ 8,000 rpm
<b>Maximum Torque</b>	48.5 lb-ft @ 6,700 rpm
<b>Fuel System</b>	DFI® with Keihin 36mm throttle bodies
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	6-speed, return shift
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System (ABS)

<b>Rear Tire</b>	160/60-17
<b>Front Brakes</b>	Dual 300mm petal-style discs with two-piston calipers (and ABS)
<b>Rear Brakes</b>	Single 220mm petal-style disc (and ABS)

## DETAILS

<b>Frame Type</b>	Trellis, high tensile steel
<b>Rake/Trail</b>	24.0° / 3.9 in
<b>Overall Length</b>	80.9 in
<b>Overall Width</b>	30.1 in
<b>Overall Height</b>	41.9 in
<b>Ground Clearance</b>	5.1 in
<b>Seat Height</b>	31.1 in
<b>Dry Weight</b>	381.5 lb** (ABS) / 379.3 lb** (non-ABS) 50-State Model
<b>Curb Weight</b>	414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model
<b>Fuel Capacity</b>	4.0 gal
<b>Wheelbase</b>	55.5 in
<b>Special Features</b>	4.3" All-digital TFT color Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
<b>Color Choices</b>	Metallic Matte Dark Gray/Metallic Spark Black, Metallic Spark Black/Green
<b>Warranty</b>	12 Month Limited Warranty

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	41mm telescopic fork/4.9 in
<b>Rear Suspension / Wheel Travel</b>	Horizontal back-link with adjustable preload, swingarm/5.1 in
<b>Front Tire</b>	120/70-17

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [panama.kawasaki-la.com](http://panama.kawasaki-la.com) for full product details.