BRUTE FORCE® 750 EPS









POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749cc

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Horsepower 50.0 hp¹ @ 6,750 rpm

Maximum Torque 42.8 lb-ft @ 4,750 rpm

Fuel System DFI® with two 34mm throttle bodies

Ignition Digital DC-CDI

Transmission Automatic Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock. shaft

CAPABILITY

Rear Tires

Front Suspension / Double wishbone, adjustable spring preload/6.9 in Wheel Travel

Rear Suspension / Double wishbone, adjustable spring preload/7.4 in Wheel Travel

Front Tires AT 25 x 8-12

Front Brakes Dual hydraulic 176mm discs with 2-piston calipers

AT 25 x 10-12

Rear Brakes Sealed, oil-bathed, multi-disc with independent park brake

Ground Clearance 9.0 in/9.7 in (max preload)

Starting System Electric
Fuel Capacity 5.0 gal

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Turning Radius 10.5 ft

Towing Capacity 1,250 lb

Total Rack Capacity 264.5 lb

Rack Capacity, Front/ 88.0/176.0 lb

Rack Capacity, Front/ Rear

Lighting All-LED lighting

DETAILS

Frame Type Double-cradle, high-tensile tubular steel
Tread Width 37.0/35.6 in
Overall Length 86.0 in

Overall Width 46.1 in

Overall Height 47.6 in

Seat Height 35.2 in

Estimated Dry Weight 685.8 lb**

Curb Weight 732.1 lb*
Wheelbase 50.6 in

Instruments Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),

battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)

Special Features Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™ system

Color Choices Grayish Blue

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit panama.kawasaki-la.com for full product details.