

ALL-NEW 2026

TERYX® 4 H2



| POWER                           |  |
|---------------------------------|--|
| Engine                          | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled   |
| Displacement                    | 999cc  |
| Maximum Horsepower              | 250.0 hp¹ @ 9,000 rpm  |
| Maximum Torque                  | 146.3 lb-ft @ 8,800 rpm  |
| Bore x Stroke                   | 73.4 x 59.0mm  |
| Compression Ratio               | 7.8:1  |
| Fuel System                     | DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger  |
| Ignition                        | TCBI with electronic advance   |
| Starting System                 | Electric   |
| Transmission                    | Automatic CVT with centrifugal clutch (H,L,N,R)  |
| Final Drive                     | Selectable 2WD/4WD with locking front differential, shaft  |
| Engine Braking                  | Yes  |
| CAPABILITY                      |  |
| Front Suspension / Wheel Travel | Double wishbone, FOX 3.0 Internal Bypass shocks, adjustable compression damping and adjustable preload/23.2 in                     |
| Rear Suspension / Wheel Travel  | 4-link trailing-arm rear suspension, FOX 3.0 Internal Bypass Shocks, adjustable compression damping and adjustable preload/24.0 in |
| Front Tires                     | Maxxis® Carnivore Plus 33 x 10.00R16   |
| Rear Tires                      | Maxxis® Carnivore Plus 33 x 10.00R16   |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion  |
| Front Brakes                    | 270mm dual hydraulic discs with 3-piston calipers  |
| Rear Brakes                     | 270mm dual hydraulic discs with 2-piston calipers  |
| Ground Clearance                | 16.5 in (max) / 16.1 in (std)  |
| Fuel Capacity                   | 14.8 gal   |

|                              |   |
|------------------------------|---|
| Turning Radius               | 24.9 ft   |
| Cargo Bed Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in                                  |
| Cargo Bed Load Capacity      | 300 lb  |
| Payload Capacity             | 1,076 lb  |
| Seating Capacity             | 4-person (2 row), bucket seats with 4-point seatbelts |
| Lighting                     | All-LED lighting                                      |

| DETAILS              |   |
|----------------------|---|
| Frame                | Ladder type, tubular steel  |
| Overall Length       | 159.4 in  |
| Overall Width        | 74.0 in   |
| Overall Height       | 71.5 in   |
| Estimated Dry Weight | 2,291.0 lb** / 2,293.2 lb** CA Model  |
| Curb Weight          | 2,425.5 lb* / 2,427.7 lb* CA Model  |
| Wheelbase            | 126.0 in  |
| Instruments          | Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/Low), Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight high-beam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp |
| Additional Features  | 7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, Steel skid-plates w/ drain holes, ERGO-FIT®, 2 DC outlets, 2 USB ports, 8 cup holders, Additional storage  |
| Color Choices        | Lime Green  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [panama.kawasaki-la.com](https://panama.kawasaki-la.com) for full product details.