ALL-NEW 2026 TERYX®4 H2









n	nı	881	FF	•
М	ш	NI	H	1

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled Engine

Displacement 999cc

Maximum Horsepower 250.0 hp1 @ 9,000 rpm **Maximum Torque** 146.3 lb-ft @ 8,800 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio

Fuel System DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki

Supercharger

Ignition TCBI with electronic advance

Starting System Electric

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Lighting **DETAILS**

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel

4-person (2 row), bucket seats with 4-point seatbelts

Overall Length 159.4 in **Overall Width** 74.0 in **Overall Height** 71.5 in

Estimated Dry Weight 2,291.0 lb** / 2,293.2 lb** CA Model **Curb Weight** 2,425.5 lb* / 2,427.7 lb* CA Model

24.9 ft

300 lb

14.6 x 33.1 x 9.1 in

All-LED lighting

Wheelbase 126.0 in

Instruments

Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/ Low), Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost

pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight highbeam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp

Additional Features

7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, Steel skid-plates w/ drain holes, ERGO-FIT®, 2 DC outlets, 2 USB ports, 8 cup holders,

Additional storage

Color Choices Lime Green

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 3.0 Internal Bypass shocks, adjustable compression damping and adjustable preload/23.2 in

4-link trailing-arm rear suspension, FOX 3.0 Internal Bypass Shocks, Rear Suspension / Wheel Travel adjustable compression damping and adjustable preload/24.0 in

Front Tires Maxxis® Carnivore Plus 33 x 10.00R16 Maxxis® Carnivore Plus 33 x 10.00R16 **Rear Tires**

Steering Electric Power Steering (EPS) / rack-and-pinion **Front Brakes** 270mm dual hydraulic discs with 3-piston calipers **Rear Brakes** 270mm dual hydraulic discs with 2-piston calipers

Ground Clearance 16.5 in (max) / 16.1 in (std)

Fuel Capacity 14.8 gal

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit panama.kawasaki-la.com for full product details.