## 2026 **Z500 ABS**









## **POWER**

**Engine** 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

**Bore x Stroke** 70.0 x 58.6mm

**Compression Ratio** 11.3:1

Maximum Horsepower 51.0 hp1 @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Economical Riding Indicator, Anti-lock Brake System

Aids

## **PERFORMANCE**

Front Suspension / **Wheel Travel** 

41mm hydraulic telescopic fork/4.7 in

**Rear Suspension / Wheel Travel** 

Horizontal back-link with adjustable spring

**Front Tire** 

preload/5.1 in

110/70-17

**Rear Tire** 150/60-17

**Front Brakes** Single 310mm semi-floating disc with 2-piston

calipers and ABS

Single 220mm disc with single-piston caliper and ABS **Rear Brakes** 

## **DETAILS**

**Frame Type** Trellis, high-tensile steel

24.5°/3.6 in Rake/Trail

**Overall Length** 78.5 in

**Overall Width** 31.5 in

**Overall Height** 41.5 in

**Ground Clearance** 5.7 in

**Seat Height** 30.9 in

**Estimated Dry** 

Weight

Wheelbase

337.4 lb\*\* 50-State Model; 335.2 lb\*\* 49-State Model

**Curb Weight** 

368.2 lb\* 50-State Model; 366.0 lb\* 49-State Model

54.1 in

**Fuel Capacity** 3.7 gal

**Special Features** 

ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Metallic Matte Graphenesteel Gray/Metallic Flat

Spark Black

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. © 2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.