Z500 SE ABS









P	N	V	V	F	R
	_			_	

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression Ratio 11.3:1

Maximum 51.0 hp1 @ 10,000 rpm

Horsepower

Maximum Torque

31.7 lb-ft @ 7,500 rpm

Fuel System DFI® with dual 32mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Economical Riding Indicator, Anti-lock Brake System

Aids

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

Front Tire 110/70-17 **Rear Tire** 150/60-17

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes Single 220mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 31.5 in

Overall Height 43.3 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry

Curb Weight

Weight

341.8 lb** 50-State Model; 339.6 lb** 49-State Model

372.6 lb* 50-State Model; 370.4 lb* 49-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, All-LED lighting, Full-color TFT

Instrumentation with Smartphone Connectivity via

RIDEOLOGY THE APP, USB-C outlet

Color Choices Pearl Blizzard White/Ebony

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. © 2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit panama.kawasaki-la.com for full product details.