

2025

# NINJA<sup>®</sup> ZX<sup>™</sup> -4RR ABS

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



METALLIC MATTE WHITISH SILVER/  
METALLIC FLAT SPARK BLACK



## POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Cilindrada	399cc
Diámetro por carrera	57.0 x 39.1mm
Relación de compresión	12.3:1
Maximum Horsepower	56.0 hp <sup>1</sup> @ 11,500 rpm
Par motor máximo	26.5 lb-ft @ 11,000 rpm
Sistema de combustible	DFI <sup>®</sup> with 34mm throttle valves (4)
Encendido	TCBI with Digital Advance
Transmisión	6-speed, return shift
Transmisión final	Chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS)

## RENDIMIENTO

Suspensión delantera/recorrido del neumático	37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in
Suspensión trasera/recorrido del neumático	Horizontal back-link, Showa BFRc lite gas-charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in

Neumático delantero	110/70-17
Neumático trasero	160/60-17
Frenos delanteros	Dual 290mm semi-floating discs with radial-mount 4-piston monobloc caliper and ABS
Frenos traseros	Single 220mm disc with single-piston caliper and ABS

## DETALLES

Tipo de chasis	Trellis, high-tensile steel
Ángulo de dirección/Avance	23.5° /3.8 in
Largo total	78.3 in
Ancho total	30.1 in
Altura del asiento	43.7 in
Distancia al suelo	5.3 in
Altura del asiento	31.5 in
Peso en orden de marcha	414.5 lb*
Depósito de combustible	4.0 gal
Distancia entre ejes	54.3 in
Características especiales	4.3" Full-color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
Colores disponibles	Metallic Matte Whitish Silver/Metallic Flat Spark Black
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [panama.kawasaki-la.com](http://panama.kawasaki-la.com) para obtener detalles completos del producto.