



ACTUALIZADA 2025

# TERYX KRX® 1000

**Kawasaki**  
Let the Good Times Roll®



-  METALLIC SIERRA BLUE/SUPER BLACK
-  METALLIC LIGHT GRAY/SUPER BLACK



## POTENCIA

Motor	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Cilindrada	999cc
Par motor máximo	76.7 lb-ft @ 7,000 rpm
Diámetro por carrer	92.0 x 75.1mm
Relación de compresión	11.5:1
Sistema de combustible	DFI® with (2) 50mm throttle bodies
Ignition	TCBI with Electronic Advance
Arranque	Electric
Transmisión	Automatic CVT with centrifugal clutch (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with locking front differential, shaft
Frenado del motor	Yes

## CAPACIDAD

Suspensión delantera / recorrido del neumático	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in
Suspensión trasera / recorrido del neumático	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in
Neumáticos delanteros	Maxxis® Carnivore 31 x 10.00R15 8PR
Neumáticos traseros	Maxxis® Carnivore 31 x 10.00R15 8PR
Dirección	Electric Power Steering (EPS) / rack-and-pinion
Frenos delanteros	Dual hydraulic discs with 2-piston calipers
Frenos traseros	Dual hydraulic discs with single-piston calipers
Distancia al suelo	14.6 in (max) / 14.0 in (std)
Depósito de combustible	10.6 gal

Radio de giro	20.3 ft
Dimensiones de la plataforma de carga (L x An x Al)	14.6 x 33.1 x 9.1 in
Capacidad de la plataforma de carga	351 lb
Capacidad de carga útil	781 lb
Asientos	2
Capacidad de remolque	N/A
Faros	(2) LED headlights, (2) LED taillights, LED stoplight

## DETALLES

Cuadro	Ladder type, tubular steel
Largo total	130.1 in
Ancho total	68.1 in
Altura total	74.8 in
Peso en orden de marcha	1,896.3 lb* / 1,898.5 lb* CA Model
Distancia entre ejes	98.8 in
Instrumental	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Características adicionales	Steel skid-plates w/ drain holes
Colores disponibles	Metallic Sierra Blue/Super Black, Metallic Light Gray/Super Black
Garantía	6 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



\*La tara incluye todos los materiales y fluidos necesarios para su correcto funcionamiento, el depósito lleno de combustible (con una capacidad superior al 90 %) y el kit de herramientas (si está incluido).  
KAWASAKI SE PREOCUPA: Lea el Manual del usuario y todas las advertencias del producto. Advertencia: Puede ser peligroso conducir un Teryx®. Para su seguridad: Lleve puesto siempre un casco, protección para los ojos y ropa adecuada. Nunca opere bajo la influencia de drogas o alcohol. Evite las velocidades excesivas y la conducción acrobática. Tenga mucho cuidado en terrenos difíciles. Proteja el medio ambiente. El Kawasaki Teryx side x side es un vehículo todoterreno únicamente y no está diseñado, equipado o fabricado para su uso en calles, carreteras o autopistas públicas. ©2024 Kawasaki Motors Corp., U.S.A. Las especificaciones están sujetas a cambios. Visite [panama.kawasaki-la.com](http://panama.kawasaki-la.com) para obtener detalles completos del producto.