

NUEVA 2025

TERYX® KRX4™ 1000

Kawasaki
Let the Good Times Roll®



-  METALLIC LIGHT GRAY/SUPER BLACK
-  METALLIC SIERRA BLUE/SUPER BLACK



POTENCIA

Motor	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Cilindrada	999cc
Par motor máximo	76.7 lb-ft @ 7,000 rpm
Diámetro por carrer	92.0 x 75.1mm
Relación de compresión	11.5:1
Sistema de combustible	DFI® with (2) 50mm throttle bodies
Ignition	TCBI with Electronic Advance
Arranque	Electric
Transmisión	Automatic CVT with centrifugal clutch (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with locking front differential, shaft
Frenado del motor	Yes

CAPACIDAD

Suspensión delantera / recorrido del neumático	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in
Suspensión trasera / recorrido del neumático	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in
Neumáticos delanteros	Maxxis® Carnivore 31 x 10.00R15 8PR
Neumáticos traseros	Maxxis® Carnivore 31 x 10.00R15 8PR
Dirección	Electric Power Steering (EPS) / rack-and-pinion
Frenos delanteros	Dual hydraulic discs with 2-piston calipers
Frenos traseros	Dual hydraulic discs with single-piston calipers
Distancia al suelo	14.8 in (max), 14.2 in (std)
Depósito de combustible	10.6 gal

Radio de giro	23.3 ft
Dimensiones de la plataforma de carga (L x An x Al)	14.6 x 33.1 x 9.1 in
Capacidad de la plataforma de carga	351 lb
Capacidad de carga útil	1,001 lb
Asientos	4
Capacidad de remolque	N/A
Faros	(2) LED headlights, (2) LED taillights, LED stoplight

DETALLES

Cuadro	Ladder type, tubular steel
Largo total	157.3 in
Ancho total	68.1 in
Altura total	76.2 in
Peso en orden de marcha	2,099.2 lb* / 2,101.4 lb* CA Model
Distancia entre ejes	125.8 in
Instrumental	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Características adicionales	Steel skid-plates w/ drain holes
Colores disponibles	Metallic Light Gray/Super Black, Metallic Sierra Blue/Super Black
Garantía	6 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite panama.kawasaki-la.com para obtener detalles completos del producto.